according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30

Revision date: 23.01.2019 Page 1 of 8

Telefax: +380 61 2228032

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

YUKO SUPER SYNTHETIC C3

SAE 5W-30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Motor oil.

1.3. Details of the supplier of the safety data sheet

Company name: JV Yukoil Ltd. Street: 3A. Bazovava

Place: Zaporozhye City, Ukraine

Telephone: +380 61 7174230

Contact person: Technical Department e-mail: info@yukoil.com
Internet: www.yukoil.com
Inquiry office: Technical Department
Emergency telephone: +380 61 2705081

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Regulation (EC) No. 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Print date: 23.01.2019

according to Regulation (EC) No 1907/2006

	YUKO SUPER SYNTHETIC C3 SAE 5W-30					
Revision date: 23.01.2019		Page 2 of 8				

Hazardous components

CAS No	Chemical name			Quantity			
	EC No	Index No	REACH No				
	Classification according to Regulation (EC) No. 1272/2008 [CLP]						
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	265-157-1		01-2119484627-25				
	Asp. Tox. 1; H304						
36878-20-3	Bis(nonylphenyl)amine				1-<5%		
	253-249-4		01-2119488911-28				
	Aquatic Chronic 4; H413						

Full text of H and EUH statements: see section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eves

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30

Revision date: 23.01.2019 Page 3 of 8

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Remove all sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30

Revision date: 23.01.2019 Page 4 of 8

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: yellow

Odour: like: mineral oil.

Test method

pH-Value: No data available

Changes in the physical state

Melting point:

No data available
Initial boiling point and boiling range:

not determined

Pour point: -40 °C ASTM D 7346 Flash point: 230 °C DIN ISO 2592

Flammability

Solid: No data available
Gas: No data available

according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30

Revision date: 23.01.2019 Page 5 of 8

Explosive properties

No data available

Lower explosion limits:No data availableUpper explosion limits:No data availableIgnition temperature:No data available

Auto-ignition temperature

Solid: No data available
Gas: No data available
Decomposition temperature: No data available

Oxidizing properties

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,854 g/cm³ DIN 51757

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient: No data available

Viscosity / kinematic: 10,1 mm²/s ASTM D 7042

(at 100 °C)

Vapour density:

Evaporation rate:

No data available

No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available

Mixture not tested.

according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30 Revision date: 23.01.2019 Page 6 of 8

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
		LD50 mg/kg	> 5000	Rat		
	dermal	LD50 mg/kg	> 2000	Rabbit		

Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Sensitising effects

Evaluation: no danger of sensitization.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-repeated exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

CAS No	Chemical name		•				
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	Acute fish toxicity	LC50 >1.000 mg/l	96 h				
	Acute algae toxicity	ErC50 >100 mg/l	72 h				

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30

Revision date: 23.01.2019 Page 7 of 8

Advice on disposal

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

Waste disposal number of waste from residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear

and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.<u>1.</u> UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group: -

Inland waterways transport (ADN)

14.<u>1.</u> UN number: -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.<u>4.</u> Packing group:

Marine transport (IMDG)

14.1. UN number: -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.<u>4.</u> Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or

mixture EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

according to Regulation (EC) No 1907/2006

YUKO SUPER SYNTHETIC C3 SAE 5W-30

Revision date: 23.01.2019 Page 8 of 8

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,7,8,9,10,14,15.

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life .

EUH210 Safety data sheet available on request.

Further Information

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Print date: 23.01.2019